

NEW PRODUCT



CLS1 High Performance Miniature Ceiling Speaker

Supplied in Pairs

The CLS1 ceiling speaker is a high performance miniature speaker system featuring a 3" polypropylene woofer and 1" aluminium tweeter. Uniquely, the CLS1 features impedance switching to allow it to be used in multiples or sound louder when needed. It is ideal for use in multi-room systems where a compact flexible solution is required.

Features

- Small footprint and shallow depth make it ideal for use where there is limited ceiling space and mounting depth available - a great solution for small rooms or corridors
- Switchable Impedance (4 or 8 ohms) - allows multiples to be installed and matched to amplifier
- Swing-tab fixings allow easy installation
- The bezel and grille can be painted to suit the décor

Specifications

- Woofer: 3" (75mm) Polypropylene cone
- Tweeter: 1" (25mm) Aluminium dome
- Frequency Response: 80Hz-20kHz
- Power Handling: 30W RMS
- Sensitivity: 84dB/1W
- Nominal Impedance: 8 or 4 ohms (switchable)
- Cutout: 130mm
- Mounting Depth: 75mm
- Colour: White Bezel and grille

NEW PRODUCT



CLS2 High Performance Ceiling Speaker

Supplied in Pairs

The CLS2 is a high quality two-way ceiling speaker suitable for all multi-room hi-fi applications

Features

- A multi-positional tweeter design that can be directed towards the listening position for best results.
- Shallow mounting depth makes it ideal for use where there is limited ceiling cavity depth
- Swing-tab fixings allow easy installation
- The bezel and grille can be painted to suit the décor

Specifications

- Bass/Mid Driver: 5 1/2" (140mm) Polypropylene cone
- Tweeter Driver: 1" (25mm) soft-dome - multi-positional
- Frequency Response: 60Hz - 20 kHz (+/- 3dB)
- Power Handling: 30W RMS
- Sensitivity: 88 dB
- Impedance: 8 ohms nominal
- Cutout: 195mm
- Mounting Depth: 75mm

NEW PRODUCT



CLS3 High Performance Ceiling Speaker

Supplied in Pairs

The CLS3 ceiling speaker is a high performance 8 1/4" speaker system featuring a polypropylene woofer and titanium tweeter. The speaker produces a dynamic full range sound with good bass extension and is intended for use where superior performance is required in multi-room applications.

Features

- A multi-positional tweeter design that can be directed towards the listening position for best results.
- Large cone woofer unit for extended bass performance - but only 90mm deep
- Shallow mounting depth makes it ideal for use where there is limited ceiling cavity depth
- Automatic overload protection
- Swing-tab fixings allow easy installation
- The bezel and grille can be painted to suit the décor

Specifications

- 8 1/4" 2 way ceiling speaker system
- Woofer: 8 1/4" (210mm) Polypropylene cone
- Tweeter: 1" (25mm) Titanium dome
- Frequency Response: 45Hz-30kHz
- Power Handling: 40W RMS
- Sensitivity: 88dB/1W
- Impedance: 8 ohms nominal
- Cutout: 245mm
- Mounting Depth: 90mm